

# Bitubo OX/AC



Tubo doble para soldadura oxiacetilencia de corte.



Tub doble per a soldadura oxiacetilència i tall.

Tubo duplo para a soldadura oxiacetilénica e corte.

Double tuyau flexible pour souder oxyacétylénique et coupe (bitube)

Tubo doppio per saldatura ossiacetilenica e taglio.

Doppelschlauch für Schweiß und Schneidarbeiten auf Sauerstoff/Acetylen-Basis.

Twin hose for welding (OX/ AC)

D. RIBAS, S.L. Bitubo OX/AC

D. RIBAS, S.L. EN559 ISO3821 20 BAR (2,0 Mpa)

# Bitubo OX Propano



Manguera doble para soldadura, corte i otros procesos afines.



Mànega doble per a soldadura, tall i altres processos afins.

Mangueira dupla para soldadura, corte e outros processos afins.

Double tuyau flexible pour souder et coupe.

Condotto doppio per saldatura, taglio e altri procedimenti simili.

Doppelschlauch für Schweiß und Schneidarbeiten und verwandte Verfahren.



Twin hose for welding (OX/PR)

D. RIBAS, S.L. Bitubo OX Propano

D. RIBAS, S.L. EN559 ISO3821 20 BAR (2,0 Mpa)

Datos técnicos

	Referencia Referência Référence Riferimento Best.-Nr.	Diámetros Diâmetros Diamètres Diametri Durchmesser		Presión Pressão Pression Pressione Druck				Radio curvatura mínimo Rádio curvatura mínimo Rayon courbure minimum Raggio di curvatura mínimo Biegeradius Min.-Wert	Peso aproximado Peso aproximado Poids approximatif Peso approssimativo Ungefähres Gewicht		
		Interior Interior Intérieur Interni Innen	Exterior Exterior Extérieur Esterno Außen	Trabajo Trabalho Travail Lavoro Arbeit	Rotura Rotura Rupture Rottura Bruch	Bar	Psi			Bar	Psi
Bitubo OX/AC	BIOXAC - 06	6 ± 0,5	(1/4)	13 ± 0,2	20	290	60	870	35	0,348	△
	BIOXAC - 08	8 ± 0,5	(5/16)	15 ± 0,2	20	290	60	870	45	0,336	□
	BIOXAC - 10	10 ± 0,5	(3/8)	17 ± 0,2	20	290	60	870	70	0,396	△
Bitubo OX Propano	BIOXPR - 06	6 ± 0,5	(1/4)	13 ± 0,2	20	290	60	870	35	0,348	□
	BIOXPR - 08	8 ± 0,5	(5/16)	15 ± 0,2	20	290	60	870	45	0,336	△



○ En Stock   □ Ocasionalmente en Stock   △ Bajo demanda